

DESK TOP W.80 Collection YES

https://www.gautieroffice.com/yes/desk-top-w-80-1



Finishes :	W: 31.5 H: 29.1 D: 31.5
	Product description :
	Metal legs I fixed, 1 cable ports in white epoxy lacquered zamak
Reference : 1U24108	Technical description :
Dimensions :	STRUCTURE • Furniture Frame: made from particleboard covered with white foil, edges wit the same finish Top and fronts: made from melamine-coated particleboard with cherrywoo
₩:80 H :74 D :80	royal oak, natural oak or white finish. 1 and 2 mm ABS edges with cherry wood, royal oal natural oak or white finish • Worktops Leg frame in steel lacquered with white RAL 9003 or grey epoxy Leg frame made from white melamine-coated particleboard • Modesty panels Separation screen: Made from particleboard covered with white foil. 2 mm ABS edges with white satin finish • Mobile 2 and 3-drawer pedestal units: In white RAL 9003 or grey epoxy lacquered steel. • Top units: Frame in melamine-coated particleboard with cherry wood, ro oak, natural oak or white finish, 2 mm ABS edges. • Fabric tops: in 12 mm particleboard covered with foam and orange, green, pink or blue fabric (100% polyester, 330gr /m ²). Fit with two magnetic strips for attaching to the metal pedestal units. • Fabric screens: in 25 fibreboard covered with foam and orange, green, pink or blue fabric (100% polyester, 330 /m ²).
	OTHER ELEMENTS • Unit trims Runners made from natural anodised aluminium. Cable housing made from through-coloured charcoal ABS. • Drawer frames Drawer frames: made from particleboard covered in black polypropylene with black roller drawer runners. Drawe frame for suspension files: made from particleboard covered with black foil, edges with the same finish, mounted on ball bearing runners, fully opening. • Doors: glazed in 4mm clear tempered glass. • Handles: made from white or grey lacquered ABS. ECOLOGY To ensure a

less than the top European standard (EN 13986).

ever cleaner environment, our company has developed low-emission panels. This collection is manufactured with wood panels containing less than 4 mg/100 g of formaldehyde - two times