

## INTERMEDIATE RECEPTION DESKTOP L. 120 CM

Collection ZOOM RECEPTION

<https://www.gautieroffice.com/zoom-reception/intermediate-reception-desktop-l-120-cm>



**Finishes :**



**Reference :** 1U29052

**Dimensions :**

**W :** 120 | **H :** 74 | **D :** 85

**W :** 48 | **H :** 30 | **D :** 34

**Product description :**

Suitable for wheelchair users.

To be positioned between 2 reception units only, ref. U29/U30.023-028-029

**Technical description :**

**STRUCTURE** • Furniture: structure in particleboard covered with white paper, edges same finish. • Reception desks: Melamine-coated particleboard body white. • Sides, top and shelves of banks, intermediate storage and reception plans suitable for disabled: chipboard melamine oak or cherrywood decor, ABS 1 and 2 mm edges oak or cherrywood decor. • Mobile pedestal units 2 and 3 drawers: RAL.9003 epoxy lacquered steel. Pen in gray PS in the mass. Black casters • Top option for mobile pedestal units: made of particleboard Thickness 18mm for options covered with melamine oak, cherrywood and white Thickness 12 mm covered with a foam and a fabric (100% polyester, 330gr/m<sup>2</sup>) orange or green or pink or blue and equipped with two magnetic strips for installation on metal boxes.

**OTHER ELEMENTS Furniture:** • Handles in white lacquered ABS. • Clear tempered glass 4 mm glass doors. • Sliding profile in natural anodized aluminum. • Anthracite ABS guide profile in the mass. • Simple lock, multi-varietal. Reception desk: • Cable tidy and cable tray in ABS lacquered grey or white in the mass. • Drawer frames made of particleboard with textile imitation effect, mounted on grey roller slides. • Drawer for suspended files standar for France and USA. Handles in white ABS in the mass. • Furniture to self-assembly except those reported with \* (fully assembled except possibly handles, skates and castors).

**ECOLOGY** To ensure an ever cleaner environment, our company has developed low-emission panels. This collection is manufactured with wood panels containing less than 4 mg/100 g of formaldehyde - two times less than the top European standard (EN 13986).